


Micro speakers


**334495**



■ Specifications

Size	φ20mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.3W
Maximum Power	0.6W
Resonance Frequency	620Hz ± 100Hz
Frequency Response	350Hz - 20kHz
Sound Pressure Level	77 0dB ± 2dB
Net Weight	2.5g


**411587**



■ Specifications

Size	φ28mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.5W
Maximum Power	1.0W
Resonance Frequency	560Hz ± 120Hz
Frequency Response	270Hz - 20kHz
Sound Pressure Level	77 5dB ± 2dB
Net Weight	5.2g


**418382**



■ Specifications

Size	φ28mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	1.0W
Maximum Power	2.0W
Resonance Frequency	600Hz ± 90Hz
Frequency Response	300Hz - 20kHz
Sound Pressure Level	79 0dB ± 2dB
Net Weight	5.1g


**022712**



■ Specifications

Size	φ32mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.5W
Maximum Power	1.0W
Resonance Frequency	540Hz ± 90Hz
Frequency Response	300Hz - 6.5kHz
Sound Pressure Level	81 0dB ± 2dB
Net Weight	6.8g


**434156**



■ Specifications

Size	φ36mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.5W
Maximum Power	1.0W
Resonance Frequency	570Hz ± 90Hz
Frequency Response	400Hz - 5.2kHz
Sound Pressure Level	83 0dB ± 2dB
Net Weight	7.5g

**022857**




■ Specifications

Size	φ40mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.5W
Maximum Power	1.0W
Resonance Frequency	470Hz ± 80Hz
Frequency Response	250Hz - 5.5kHz
Sound Pressure Level	81 5dB ± 2dB
Net Weight	8.5g

Micro speakers


420998



■ Specifications

Size	φ45mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	1.5W
Maximum Power	3.0W
Resonance Frequency	600Hz ± 100Hz
Frequency Response	300Hz - 5kHz
Sound Pressure Level	82.0dB ± 2dB
Net Weight	12.5g


022948



■ Specifications

Size	φ50mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	0.5W
Maximum Power	1.0W
Resonance Frequency	390Hz ± 60Hz
Frequency Response	250Hz - 4kHz
Sound Pressure Level	88.5dB ± 2dB
Net Weight	16.9g


043961



■ Specifications

Size	40 x 20mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	1.0W
Maximum Power	2.0W
Resonance Frequency	480Hz ± 96Hz
Frequency Response	260Hz - 20kHz
Sound Pressure Level	79.5dB ± 2dB
Net Weight	6.9g

421029




■ Specifications

Size	40 x 28.5mm
Type	Dynamic
Impedance	8.0Ω ± 15%
Nominal Power	1.0W
Maximum Power	—
Resonance Frequency	485Hz ± 100Hz
Frequency Response	220Hz - 3.2kHz
Sound Pressure Level	78.5dB ± 2dB
Net Weight	8.7g

USB speaker

628421



■ Specifications

Speaker driver	φ50mm
Sound Pressure Level	93dB (@1kHz, 0dBFS)
Water Proof	IPX5
Dust Proof	IP4 / IP5
Input	USB A Type (USB audio class 1.0 or more)
Current Usage	200mA (@ 1kHz, 0dBFS)
Net Weight	90g

Contact Information

お問い合わせ先

If you have any inquiry about micro speakers, please contact us below.  
 小型スピーカに関するお問い合わせは、下記までご連絡ください。

E-Mail :marketing@foster.co.jp